



floor drain DallDrain Pure, DN 50, 120 x 120 mm

Part number: 517029
 GTIN: 4001636517029
 Rebate group: 6



Description:

floor drain DallDrain Pure, DN 50, 120 x 120 mm
 conforming to DIN EN 1253

Floor drain including grating DallDrain Pure with stainless steel grate in plastic frame. Side outlet DN 50, with ball joint, adjustable from 0 – 15 degrees.

Specification

- Stainless steel grate, plastic frame
- Integrated screed anchoring
- Flexible, click-in sealing sleeve for secure connection to bonded and sheet waterproofing conforming to DIN 18534
- Fully removable, two-piece trap insert and rodding eye, 50 mm water seal (conforming to DIN EN 1253)
- Temporary blanking plate
- Three sound-insulated mounting feet for fixing and height adjustment 85 – 250 mm
- Spigot can be shortened for floorings 10 – 36 mm (including adhesive)

Material

Polypropylene drain body and outlet, highly impact-resistant;
 1.4301 stainless steel grate, load class K 3 (300 kg); spigot and frame in ABS
 Pre-assembled set consisting of parts no. 517289 + 517210 + 517340.

Grating with positioning aid laterally adjustable +/- 9.5 mm.
 Can be used with sound insulation mat DallDrain (part no. 517326) and

mounting aid DallDrain (part no. 517319).

Flow rates tested to DIN EN 1253:

Nominal diameter	Product standard	Min. flow rate according to norm	Water level according to norm	Flow rate at water level 10 mm	Flow rate at water level 20 mm
DN 50	DIN EN 1253	0.80 l/s	20.00 mm	0.65 l/s	0.92 l/s

09.12.2023 04:05

DALLMER

Spare parts:

501080 grate E 115, 115 x 115 mm

517289 grating DallDrain Pure, 120 x 120 mm

517340 mounting feet DallDrain

517357 trap insert DallDrain

517197 sealing sleeve DallDrain